

WELLHEAD

Wellhead

PPGL supplies high quality wellhead products, such as, Christmas trees, casing head, tubing head, and other auxiliary equipments suitable for land and offshore applications to explore, develop and produce oil.

Our wellhead and Christmas tree Designing, manufacturing, testing and control are all in accordance with API 6A, can be used to replace FMC wellhead products.

The wellheads are available in pressure rating up to 15,000PSI, load rating up to 500 tons, material classes from AA through FF, temperature classes from L through V, product specification levels from 1 through 4 and PR1 & 2, and also meet NACE Standard MR0175.




Wellhead Assembly

Technical Specifications of Wellhead Assembly

Wellhead Assembly		Wellhead Assembly						
		PPGL-WS 65/21	PPGL-WS 65/35	PPGL-WS 80-65/35	PPGL-WS 65/70	PPGL-WS 78-65/70	PPGL-WS 65/105	PPGL-WS 78-65/105
Rated Pressure (psi)		3,000	5,000	5,000	10,000	10,000	15,000	15,000
Nominal Size	Main (in)	2-9/16	2-9/16	3-1/8	2-9/16	3-1/16	2-9/16	3-1/16
	Side (in)	2-9/16	2-9/16	2-9/16	2-9/16	2-9/16	2-9/16	2-9/16
Working Temperature		P U						
Available Medium		Crude Gas						
PSL		PSL1~3						
Material Class		AA~FF						
PR		PR1~2						
Connection Type		Clamp, Flanged			Flanged			

Christmas Tree




Christmas Tree

Christmas Tree Components:




Flanged Cross



Double Studded Adapter



Tubing Head Adapter



Studded Cross

Technical Specifications of Christmas Tree

Christmas Tree Parameter	Christmas Tree	
	PPGL-CT65/25	PPGL-CT 65/60
Rated Pressure (psi)	3,500	8,500
Nominal Size (in)	2-	2-9/16
Working Temperature	P U	P U
Available Medium	Crude, Water	Crude, Water
Connection Type	Flanged Connection	Flanged Connection
Material Class	AA~DD	AA~FF
PSL	PSL1~2	PSL1~3
PR	PR1~2	PR1~2

Casing Head



Casing Head

Technical Specifications of Casing Head

Casing Head Paramet	Casing Head Type		
	PPGL-BW 5-1/2~20	PPGL-BS 5-1/2~30	PPGL-BT 5-1/2~20
Connection type	Bottom Welded Type	Bottom Slip Type and Double seal Structure	Bottom threads connection
Casing Size (in)	5-1/2, 7, 9-5/8, 20	5-1/2, 7, 9-5/8, 12-1/4, 13-3/8, 20, 30	5-1/2, 7, 9-5/8", 13-3/8, 20

Tubing Head



Tubing Head

Technical Specifications of Tubing Head

Tubing Head	PPGL-TH7-1/16~13-5/8
Nominal Dia.(in)	7-1/16 ~ 13-5/8
Working	2,000~20,000PSI
Temperature	- 60°C ~ +121°C (K,U)
Range	PSL1~4, PR1~2, AA ~ FF