

DOUBLE STUDDED ADAPTER FLANGE

Double Studded Adapter Flange (DSAF)

DSAF (Double Studded Adapter Flange) is a combination of flanges of different sizes and pressure ratings. PPGL supplies DSAF (Double Studded Adapter Flange) in various sizes and pressure ratings as per customer's specified thickness, consistent with design considerations.



DSAF (Double Studded Adapter Flange) range:

Size: As per customer's requirement

Pressure rating: 2,000PSI to 15,000PSI

Material of construction: As per API 16A

Service condition: General, Sour services

Double Studded Adapter Flange

Technical Specifications of DSAF (Double Studded Adapter Flange)

DSAF	Flange thickness (T) (mm)
2-1/16" x 5M To 3-1/8" x 5M	70
2-1/16" x 10M To 4-1/16" x 10M	80
3-1/16" x 10M To 4-1/16" x 10M	130
3-1/16" x 10M To 4-1/16" x 5M	80
4-1/16" x 5M To 2-1/16" x 5M	75
4-1/16" x 5M To 3-1/8" x 5M	83
4-1/16" x 2M To 4-1/16" x 5M	80
7-1/16" x 10M To 13-5/8" x 10M	170
7-1/16" x 5M To 13-5/8" x 5M	150
11" x 15M To 18-3/4" x 15M	256
11" x 5M To 13-5/8" x 5M	144
13-5/8" x 10M To 11" x 10M	267
13-5/8" x 3M To 16-3/4" x 2M	150
13-5/8" x 10M To 18-3/4" x 15M	256
13-5/8" x 5M To 18-3/4" x 15M	256
18-3/4" x 15M To 20-3/4" x 3M	270
20-3/4" x 3M To 18-3/4" x 15M	256
21-1/4" x 2M To 18-3/4" x 15M	256