

WASHOVER PIPE

Washover Pipe

Wash over pipe is one special tool to solve sticking pipe. It has a two-step, double-shouldered thread joint with flush outside and inside diameters.

This buttress-type thread of wash over pipe assures quick make-up and high torsion strength. Size of wash over pipe is available ranging from 3 1/2 to 20 inches in O.D. Contact PPGL for such wash over pipe.



Washover Pipe

Technical Specifications of Washover Pipe

Washover Pipe Model	OD mm (in)	ID (mm)	W.T. (mm)	Min. Well hole (mm)	Max. Wash size (mm)
PPGL-WP114.3-8.56	Φ114.30 (4 ^{1/2})	Φ97.18	8.56	Φ120.65	Φ88.90
PPGL-WP 146.05-9	Φ146.05 (5 ^{3/4})	Φ128.05	9.00	Φ161.93	Φ120.65
PPGL-WP 193.68-12.7	Φ193.68 (7 ^{5/8})	Φ168.28	12.70	Φ212.73	Φ161.93
PPGL-WP 203.2-9.53	Φ203.20 (8)	Φ184.15	9.53	Φ215.90	Φ177.80
PPGL-WP 206.38-10.67	Φ206.38 (8 ^{1/8})	Φ185.04	10.67	Φ215.90	Φ177.80
PPGL-WP 219.07-12.7	Φ219.07 (8 ^{5/8})	Φ193.67	12.70	Φ244.48	Φ184.15
PPGL-WP 228.6-10.8	Φ228.60 (9)	Φ207.01	10.80	Φ250.83	Φ200.03
PPGL-WP 244.48-11.99	Φ244.48 (9 ^{5/8})	Φ220.50	11.99	Φ266.70	Φ206.37
PPGL-WP 273.05-12.57	Φ273.05 (10 ^{3/4})	Φ247.91	12.57	Φ298.45	Φ234.95
PPGL-WP 339.72-12.10	Φ339.72 (13 ^{3/8})	Φ315.52	12.10	Φ365.13	Φ301.62