

Strainer

Y-type Strainer

Main Technical Specifications

Design and Manufacture	ASME B16.34
Face to Face Dimension	ASME B16.10, EN 558, DIN 3202
Flange Connection Dimension	ASME B16.5, DIN 2501
BW Connection Dimension	ASME B16.25
Pressure-Temperature Ratings	ASME B16.34
Test and Inspection	API 598
Nominal Diameter	2" ~ 36"
Nominal Pressure(Class)	150Lb ~ 900Lb
Main Materials	WCB, WCA, WCC, WC6, WC9, LCB, LCC, C5, C12, CF8, CF8M, CF3, CF3M, CF8C, CN7M



Y-type Pressure Sealed Strainer

Main Technical Specifications

Design and Manufacture	ASME B16.34
Face to Face Dimension	ASME B16.10, EN 558, DIN 3202
Flange Connection Dimension	ASME B16.5, DIN 2501
BW Connection Dimension	ASME B16.25
Pressure-Temperature Ratings	ASME B16.34
Test and Inspection	API 598
Nominal Diameter	2" ~ 36"
Nominal Pressure(Class)	900Lb ~ 2500Lb
Main Materials	WCB, WCA, WCC, WC6, WC9, LCB, LCC, C5, C12, CF8, CF8M, CF3, CF3M, CF8C, CN7M



Basket Strainer

Main Technical specifications

Design and Manufacture	ASME B16.34
Face to Face Dimension	ASME B16.10, EN 558, DIN 3202
Flange Connection Dimension	ASME B16.5, DIN 2501
BW Connection Dimension	ASME B16.25
Pressure-Temperature Ratings	ASME B16.34
Test and Inspection	API 598
Nominal Diameter	2" ~ 36"
Nominal Pressure(Class)	150Lb ~ 900Lb
Main Materials	WCB, WCA, WCC, WC6, WC9, LCB, LCC, C5, C12, CF8, CF8M, CF3, CF3M, CF8C, CN7M

